

Ø60



PROFILES & INFILL PANELS



code	type
09.60100-9999	profile Ø60 RAL


when using only LED inserts, the correct length = (number of inserts * 280) + 34mm
 bij gebruik van enkel LED modules, is de correcte lengte = (aantal modules * 280) + 34mm
 en cas d'utilisation de que des modules de LED, la longueur correcte = (nombre de modules * 280) + 34mm
 wenn nur LED Einsätze verwendet werden, ist die richtige Länge = (Anzahl der Einsätze * 280) + 34mm




code	type
09.60101-9999	infill panel RAL

is necessary where there is no LED diffuser or track foreseen
 is nodig waar er geen LED afscherming of rail is voorzien
 est nécessaire là où il n'y a pas de diffuseur LED ou du rail
 ist notwendig wo keine LED Abdeckung oder Stromschiene vorgesehen ist

END CAPS & CORNERS



code	type
01.60183-9999	end cap RAL




code	type
01.60160-0005	In-line coupler 180°



code	type
01.60110-9999	L-corner 90°
01.60100-9999	2way-corner 45-179°

corners are separate pieces, not mitre cut
 hoeken zijn aparte onderdelen, niet in verstek gezaagd
 raccords sont des pièces séparées, pas coupés en biais
 Verbindungsteile sind separate Teile, nicht auf Gehrung geschnitten





code	type
01.60130-9999	T-corner 2x90°
01.60104-9999	3way-corner 3x45-270°

corners are separate pieces, not mitre cut
 hoeken zijn aparte onderdelen, niet in verstek gezaagd
 raccords sont des pièces séparées, pas coupés en biais
 Verbindungsteile sind separate Teile, nicht auf Gehrung geschnitten



9999=any RAL colour powder coated
 elke RAL kleur poederlak
 chaque teinte RAL peint-par-poudrage
 jede RAL Farbe pulverbeschichtet




code	type
01.60140-9999	X-corner 4x90°
01.60105-9999	4way-corner 4x45-225°

corners are separate pieces, not mitre cut
 hoeken zijn aparte onderdelen, niet in verstek gezaagd
 raccords sont des pièces séparées, pas coupés en biais
 Verbindungsteile sind separate Teile, nicht auf Gehrung geschnitten


3-CIRCUIT TRACK




code	type
09.60104-0000	grey track
09.60105-0000	black track
09.60106-0000	white track
09.60144-0000	grey track DALI
09.60145-0000	black track DALI
09.60146-0000	white track DALI



code	type
27.00310-7040	grey track supply left side
27.00310-9005	black track supply left side
27.00310-9010	white track supply left side
27.00340-7040	grey track supply left side DALI
27.00340-9005	black track supply left side DALI
27.00340-9010	white track supply left side DALI



code	type
27.00311-7040	grey track supply right side
27.00311-9005	black track supply right side
27.00311-9010	white track supply right side
27.00341-7040	grey track supply right side DALI
27.00341-9005	black track supply right side DALI
27.00341-9010	white track supply right side DALI



code	type
27.00315-7040	grey end cap
27.00315-9005	black end cap
27.00315-9010	white end cap
27.00315-7040	grey end cap DALI
27.00315-9005	black end cap DALI
27.00315-9010	white end cap DALI




9999=any RAL colour powder coated
 elke RAL kleur poederlak
 chaque teinte RAL peint-par-poudrage
 jede RAL Farbe pulverbeschichtet



code	type
27.00320-7040	grey straight coupler
27.00320-9005	black straight coupler
27.00320-9010	white straight coupler
27.00350-7040	grey straight coupler DALI
27.00350-9005	black straight coupler DALI
27.00350-9010	white straight coupler DALI

LED INSERTS



code	type
27.60608-4030	LED insert HO - L70mm - 0,25 insert
27.60601-4030	LED insert HO - L140mm - 0,5 insert
27.60611-4030	LED insert HO - L280mm - 1 insert
27.60621-4030	LED insert HO - L560mm - 2 inserts
27.60631-4030	LED insert HO - L840mm - 3 inserts
27.60641-4030	LED insert HO - L1120mm - 4 inserts
27.60651-4030	LED insert HO - L1400mm - 5 inserts

LO = low output, HO = high output

CRI >80
 CRI>90 on request
 CRI>90 op aanvraag
 CRI>90 sur demande
 CRI>90 auf Anfrage



code	type	dim
27.600091w-0625	LED driver 25W	-
27.600091w-0650	LED driver 50W	-
27.600091w-0675	LED driver 75W	-
27.600091w-0825	LED driver 25W	DALI/TD
27.600091w-0850	LED driver 50W	DALI/TD
27.600091w-0875	LED driver 75W	DALI/TD

LO = low output, HO = high output, TD = touch-dim, 1-10V on request

for each type of driver, the code to be entered (W), the current (mA), the lumen value and the range are displayed. Choose the suitable driver based on the number of LED inserts (=range) and the lumen value - per type driver worden de in te vullen code (W), aansturing (mA), lumenwaarde en het bereik weergegeven. Kies de geschikte driver op basis van het aantal LED modules (=bereik) en de lumenwaarde - pour chaque type de driver, le code à choisir (W), le courant (mA), la valeur de lumen et la portée sont présentés. Choisissez le driver approprié en fonction du nombre de modules LED (=la portée) et la valeur de lumen - für jeden Treibertyp werden der einzugebende Code (W), die Ansteuerung (mA), der Lumenwert und der Bereich angezeigt. Wählen Sie den geeigneten Treiber gemäß der Anzahl LED Einsätze (=Bereich) und dem Lumenwert

	HO W=1 150mA 3,2W 670lm/280mm # inserts	HO W=3 325mA 7,2W 1340lm/280mm # inserts
27.600091w-0625	1 - 2	1 - 2
27.600091w-0650	2,5 - 6,25	2,5 - 6
27.600091w-0675	6,5 - 9,75	6,25 - 9,5
27.600091w-0825	1 - 2,25	1 - 2,25
27.600091w-0850	2,5 - 6,25	2,5 - 6
27.600091w-0875	6,5 - 9,75	6,25 - 9,5




27= 2700K
 30= 3000K
 40= 4000K

for more information about the LED inserts, see pages 428-429
 voor meer informatie over de LED modules zie pagina's 428-429
 pour plus d'informations sur les modules LED, voir pages 428-429
 für mehr Informationen zu den LED Einsätzen, siehe Seiten 428-429







code

type

27.60631-9030
27.60641-9030
27.60651-9030


LED TW 2700-6500K 41,1W 4500lm HO - L840mm
LED TW 2700-6500K 54,1W 6000lm HO - L1120mm
LED TW 2700-6500K 67,3W 7500lm HO - L1400mm

**CRI
>90**

HO = high output, TW = tunable white

DALI driver type 8 included · Inclusief DALI driver type 8 · driver DALI type 8 inclus · inklusive DALI Treiber Typ 8
type 6 on request · type 6 op aanvraag · type 6 sur demande · Typ 6 auf Anfrage

LED DIFFUSERS



h=91% CIE 43 72 90 94 91

code

type

02.60800-0000

satin LED diffuser

EMERGENCY MODULES



code

type

27.60290-0000
27.60291-0000
27.60292-0000
27.60293-0000

LED emergency 1h 350lm - selftest
LED emergency 3h 350lm - selftest
LED emergency 1h 350lm - selftest DALI
LED emergency 3h 350lm - selftest DALI



only applicable from 4 LED inserts (1h - selftest) or 6 LED inserts (3h - selftest) · min. 280-max. 560mm per driver in case of emergency

enkel geschikt vanaf 4 LED modules (1h - selftest) of 6 LED modules (3h - selftest) · min. 280-max. 560mm per driver in noodtoestand

seulement utilisable à partir de 4 modules LED (1h - selftest) ou 6 modules LED (3h - selftest) · min. 280-max. 560mm par driver en configuration secours

nur geeignet ab 4 LED Einsätzen (1h - selftest) oder 6 LED Einsätzen (3h - selftest) · min. 280-max. 560mm pro Treiber im Notstand

ACCESSORIES



code

type

27.600132-9999
27.600232-9999
27.600133-9999
27.600233-9999
27.600134-9999
27.600234-9999

LED downlight 3x1W 2700K 357lm 8°
LED downlight 3x1W 2700K 357lm 32°
LED downlight 3x1W 3000K 378lm 8°
LED downlight 3x1W 3000K 378lm 32°
LED downlight 3x1W 4000K 399lm 8°
LED downlight 3x1W 4000K 399lm 32°

order drivers separately · voedingen apart bestellen · commandez l'alimentation séparément · Treiber separat bestellen




9999=any RAL colour powder coated

elke RAL kleur poederlak

chaque teinte RAL peint-par-poudrage

jede RAL Farbe pulverbeschichtet




code	type
27.600142-9999	LED downlight 4x1W 2700K 476lm 8°
27.600242-9999	LED downlight 4x1W 2700K 476lm 32°
27.600143-9999	LED downlight 4x1W 3000K 504lm 8°
27.600243-9999	LED downlight 4x1W 3000K 504lm 32°
27.600144-9999	LED downlight 4x1W 4000K 532lm 8°
27.600244-9999	LED downlight 4x1W 4000K 532lm 32°

order drivers separately · voedingen apart bestellen · commandez l'alimentation séparément · Treiber separat bestellen



code	type	dim	3x1W-350mA # downlights	4x1W-350mA # downlights
27.6000917-0608	LED driver 8W	-	1-2	1
27.6000917-0625	LED driver 25W	-	3-5	2-4
27.6000917-0650	LED driver 50W	-	6-14	5-10
27.6000917-0810	LED driver 10W	DALI	1-3	1-2
27.6000917-0825	LED driver 25W	DALI/TD	3-5	2-4
27.6000917-0850	LED driver 50W	DALI/TD	6-14	5-10

TD = touch-dim



code	type
27.000152-9999	spot 5W 2700K 482lm 10°
27.000252-9999	spot 5W 2700K 482lm 25°
27.000352-9999	spot 5W 2700K 482lm 40°
27.000153-9999	spot 5W 3000K 500lm 10°
27.000253-9999	spot 5W 3000K 500lm 25°
27.000353-9999	spot 5W 3000K 500lm 40°
27.000154-9999	spot 5W 4000K 532lm 10°
27.000254-9999	spot 5W 4000K 532lm 25°
27.000354-9999	spot 5W 4000K 532lm 40°



**CRI
>90**

order drivers separately · voedingen apart bestellen · commandez l'alimentation séparément · Treiber separat bestellen



code	type	dim	5W-200mA # spots
27.6000916-0625	LED driver 25W	-	1-2
27.6000916-0650	LED driver 50W	-	3-5
27.6000916-0825	LED driver 25W	DALI/TD	1-2
27.6000916-0850	LED driver 50W	DALI/TD	3-5

TD = touch-dim




code	type
27.00040-9005	push switch ON/OFF 250V/10Amp
27.00041-9005	push switch ON/OFF+dimming 250V/10Amp

27.00041-9005 only with DALI/TD dimmable insert, max. 4 drivers per push switch
 27.00041-9005 enkel met DALI/TD dimbare module, max. 4 drivers per drukknop
 27.00041-9005 seulement avec module dimmable DALI/TD, 4 drivers par bouton poussoir au maximum
 27.00041-9005 nur mit DALI/TD dimmbarem Einsatz, Maximal 4 Treiber pro Druckknopf



9999=any RAL colour powder coated
 elke RAL kleur poederlak
 chaque teinte RAL peint-par-poudrage
 jede RAL Farbe pulverbeschichtet



code	type
27.60105-0000	motion detector max. 2 drivers


stand-alone system that cannot be connected in parallel

code	type
27.60106-0000	white daylight and/or motion detector – max. 2x 5 drivers
27.60106-9005	black daylight and/or motion detector – max. 2x 5 drivers

only with DALI dimmable insert · enkel met DALI dimbare module · seulement avec module dimmable DALI · nur mit DALI dimmbarem Einsatz

including remote control for on/off + dimming
 inclusief afstandsbediening voor aan/uit + dimmen
 commande inclus pour allumer/éteindre + régler l'intensité de la lumière
 Fernbedienung einbegriffen um ein-/aus zu schalten + zu dimmen

stand-alone system that cannot be connected in parallel




code	type
22.99122-0000	remote control


to order together with the daylight & motion detector (27.60106-0000)

remote control suitable for extensive configuration of sensor (only motion, only daylight or both,...)
 afstandsbediening geschikt voor uitgebreide instelling van sensor (enkel beweging, enkel daglicht of beide,...)
 commande appropriée pour le réglage du détecteur (seulement du mouvement, seulement de la lumière du jour ou tous les deux,...)
 Fernbedienung geeignet für ausführliche Einstellung des Sensors (nur Bewegung, nur Tageslicht oder beide,...)

FIXATIONS



code	type
01.60175-9999	wall support around the profile



code	type
03.99400-9999	base for direct mounting



9999=any RAL colour powder coated
 elke RAL kleur poederlak
 chaque teinte RAL peint-par-poudrage
 jede RAL Farbe pulverbeschichtet

SUSPENSIONS & CABLES




code	type
03.99100-2400	steelwire suspension type 1 – L1800mm
03.99100-4700	steelwire suspension type 1 – L4500mm

steelwire is adjustable via cylinder on the ceiling
 staaldraad is verstelbaar via cilinder aan het plafond
 le fil d'acier est réglable par le cylindre au plafond
 Stahldraht ist über den Zylinder an der Decke verstellbar




code	type
03.99113-2400	black steelwire suspension type 1 – L1800mm
03.99113-4700	black steelwire suspension type 1 – L4500mm

steelwire is adjustable via cylinder on the ceiling
 staaldraad is verstelbaar via cilinder aan het plafond
 le fil d'acier est réglable par le cylindre au plafond
 Stahldraht ist über den Zylinder an der Decke verstellbar




code	type
03.99110-2400	steelwire suspension type 2 – L1800mm
03.99110-4700	steelwire suspension type 2 – L4500mm


steelwire is adjustable on the profile
 staaldraad is verstelbaar aan het profiel
 le fil d'acier est réglable au profil
 Stahldraht ist am Profil verstellbar



code	type
03.99183-0000	steelwire suspension pivotable – L1800mm
03.99185-0000	steelwire suspension pivotable – L4500mm




code	type
03.99506-9999	power cable 3x0,75mm ² – L1800mm
03.99518-9999	power cable 3x1,5mm ² – L1800mm
03.99538-9999	power cable 5x0,75mm ² – L1800mm
03.99528-9999	power cable 5x1,5mm ² – L1800mm
03.99507-9999	power cable 3x0,75mm ² – L4500mm
03.99519-9999	power cable 3x1,5mm ² – L4500mm
03.99539-9999	power cable 5x0,75mm ² – L4500mm
03.99529-9999	power cable 5x1,5mm ² – L4500mm



code	type
03.99210-9999	rod suspension – L600mm
03.99230-9999	rod suspension – L1000mm



9999=any RAL colour powder coated
 elke RAL kleur poederlak
 chaque teinte RAL peint-par-poudrage
 jede RAL Farbe pulverbeschichtet



code

03.99206-9999
03.99226-9999

type

rod suspension incl. 3x1,5mm² - L600mm
rod suspension incl. 3x1,5mm² - L1000mm

ADDITIONAL WIRING




standard wiring

standaard bedrading
câblage standard
standard Verdrahtung

1 switching circuit with 3 cables 1,5mm²: L = phase (brown), N = neutral (blue), earthing (yellow-green)

1 schakelkring met 3 kabels 1,5mm²: L = fase (bruin), N = nulleider (blauw), aarding (geel-groen)
1 circuit avec 3 câbles 1,5mm²: L = phase (brun), N = neutre (bleu), terre (jaune-vert)
1 Schaltkreis mit 3 Kabeln 1,5mm²: L = Phase (braun), N = Nulleiter (blau), Erdung (gelb-grün)



code

23.00099-1150
23.00099-2075
23.00099-2150

type

1 cable 1,5mm² for additional switching circuit (grey or orange or violet)
2 cables 0,75mm² for dimming (black & red)
2 cables 1,5mm² for emergency module supply (white & blue)



9999=any RAL colour powder coated

elke RAL kleur poederlak

chaque teinte RAL peint-par-poudrage

jede RAL Farbe pulverbeschichtet

