

Score flat Direct/Indirect - satin - HO 325mA - RAL  
04.87100694-9999

#### Fixture details

|                 |                           |
|-----------------|---------------------------|
| Mounting        | Pendant                   |
| Light emission  | Direct-Indirect           |
| Fitting cover   | satin diffusor            |
| Protection rate | IP 20                     |
| Housing         | Aluminium                 |
| Finish          | RAL colour at your choice |
| Certificates    | CE, ISO 9001              |

#### Electric details

|                  |                |
|------------------|----------------|
| Protection class | I              |
| Supply           | 230V           |
| Control gear box | Current driver |

#### Lamp details

|                     |                   |
|---------------------|-------------------|
| Lamptype            | LED 4000K         |
| Wattage             | 7,1W              |
| Gross luminous flux | 24225             |
| Luminaire power     | 133,6W            |
| Number              | 17                |
| Lifetime LED module | L80/B10 > 102000h |
| Color tolerance     | MacAdam 3         |
| CRI                 | >80               |

#### Photometric details

|                       |                |
|-----------------------|----------------|
| UGR                   | >19            |
| CIE Fluxcode          | 56 88 98 99 71 |
| CIE Fluxcode Indirect | 00 00 00 00 73 |

#### Dimensions

|   |         |
|---|---------|
| A | 2544 mm |
|---|---------|

#### Remarks

Suspended luminaire - Direct/Indirect - HO 325mA - satin - RAL






Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015